ALTV615DC48ULM
UL Listed DC CCTV Power Supply

Rev. DSALTV615DC48ULM - 01052012

ALTV615DC48ULM

Overview

ALTV615DC48ULM provides 6VDC to 15VDC distributed via eight (8) Class 2 Rated fuse protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- Input 115VAC, 50/60 Hz, 0.9 amp.

Output:

- Eight (8) Class 2 Rated fuse protected power limited outputs.
- 6VDC to 15VDC field adjustable.
- 4 amp total continuous supply current *(0.5 amp per device, 3.5 amp max.).*
- Output fuses are rated @ 3.5 amp/250VAC.
- Filtered and electronically regulated outputs.

Electrical:

- Operating temperature: 0º C to 49º C ambient.
- 9-23 BTU/Hr.
- System AC input VA requirement: 103.5VA.

Mechanical:

- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.): 8.5” (215.9mm) x 7.5” (190.5mm) x 3.75” (95.25mm)
- Product weight (approx.): 8.65 lbs. (3.92 kg.).
- Shipping weight (approx.): 9.15 lbs. (4.15 kg.).

Features:

- AC input and DC output LED indicators.
- Power ON/OFF switch.
- Spare fuse(s) provided.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

Agency Approvals

UL Listed for Commercial CCTV Equipment (UL 2044).

CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

Enclosure Dimensions *(H x W x D) (approximate)*:

8.5” (215.9mm) x 7.5” (190.5mm) x 3.75” (95.25mm)